


150W Single Output for Telecom



- Wide AC input range
- Wide operating temperature
- Built-in lightningproof 3000A (8/20us)
- AC input failure signal (option)
- Protections: over current/ over voltage/ short circuit
- 2 years warranty
- N615 199 x 98 x 50(mm)

AC input voltage range	160~280VAC (210~370VDC) 85~132/170~280VAC selected by switch(option)
Input frequency	47~63Hz
Inrush current	cold start, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	$\leq \pm 0.5\%$
Output voltage adjust range	$\pm 10\%$
Output over current protection	110~130%
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 3.0KVAC/1min (gas tube must be deleted when test) I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-20°C~+60°C, 20%~93%RH (non condensing)
Storage temp. & humidity	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards	design meet GB4943, UL60950, EN60950
EMC standards	design meet GB9254, EN55022 classB EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		Load regul.	R&N	Efficiency
NO150W-ST-12	12V	12.5A	0.5%	120mV	82%
NO150W-ST-13.5	13.5V	11.1A	0.5%	120mV	82%
NO150W-ST-24	24V	6.3A	0.5%	150mV	83%
NO150W-ST-27	27V	5.6A	0.5%	150mV	83%
NO150W-ST-48	48V	3.1A	0.5%	200mV	86%

Drawing

