


200W Dual Output for Telecom



- Wide AC input range
- Wide operating temperature
- Built-in lightningproof 3000A (8/20us)
- AC input failure signal (option)
- Protections: over current/ over voltage/ short circuit
- 2 years warranty
- N620 200 x 110 x 50(mm)

AC input voltage range	160~280VAC (210~370VDC)
Input frequency	47~63Hz
Inrush current	cold start, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	≤ ± 0.5%
Output voltage adjust range	V _i : ± 5% of rated output voltage
Output over current protection	110~130%
Output over voltage protection	115~150%
Withstand voltage	I/P -O/P: 3.0KVAC/1min
<i>(gas tube must be deleted when test)</i>	I/P -F/G: 1.5KVAC/1min
	O/P-F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-20°C~+60°C, 20%~93%RH (non condensing)
Storage temp. & humidity	-20°C~+85°C, 20%~95%RH (non condensing)
Safety standards	design meet GB4943, UL60950, EN60950
EMC standards	design meet GB9254, EN55022 classA
Cooling method	convection

Model	DC Output		Load regul.	R&N	Efficiency
NO200W-DT-A	27V	6.0A	0.5%	150mV	82%
	9V	3.0A	3.0%	100mV	
NO200W-DT-B	27V	6.0A	0.5%	150mV	83%
	12V	3.0A	3.0%	120mV	
NO200W-DT-C	24V	6.8A	0.5%	150mV	82%
	12V	3.0A	3.0%	120mV	

Drawing

