

35W Single Output Series



- High reliability, low cost
- Built-in EMI filter
- 100% full load burn-in test
- Protections: overload/ short circuit
- 1 year warranty
- N603 129 x 98 x 40(mm)

| | |
|-----------------------------------|---|
| AC input voltage range | 170~264VAC (210~370VDC) |
| Input frequency | 47~63Hz |
| Inrush current | cold start, 40A/230V |
| Input leakage current | < 0.5mA/ 230VAC |
| Line regulation (full load) | ≤ ± 0.5% |
| Output voltage adjust range | ± 10% |
| Output overload protection | 110~150% |
| Withstand voltage | I/P -O/P: 1.5KVAC/1min I/P -F/G: 1.5KVAC/1min O/P-F/G: 0.5KVAC/1min |
| Rise time | 50ms@full load (typical) |
| Hold up time | 20ms@full load (typical) |
| Operating temp. & humidity | -10°C~+50°C, 20%~90%RH (non condensing) |
| Storage temp. & humidity | -20°C~+85°C, 20%~95%RH (non condensing) |
| Safety standards | design meet GB4943, UL60950, EN60950 |
| EMC standards | design meet GB9254, EN55022 classA EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11 |
| Cooling method | convection |

| Model | DC Output | | Load regul. | R&N | Efficiency |
|------------|-----------|------|-------------|-------|------------|
| NO35W-S-5 | 5V | 7.0A | 0.5% | 60mV | 72% |
| NO35W-S-12 | 12V | 3.0A | 0.5% | 80mV | 74% |
| NO35W-S-15 | 15V | 2.4A | 0.5% | 100mV | 76% |
| NO35W-S-24 | 24V | 1.5A | 0.5% | 100mV | 78% |
| NO35W-S-48 | 48V | 0.7A | 0.5% | 150mV | 79% |

* 3~48VDC output all available.

Drawing

